

Field Sprayers 400 - 1000 Litre Specification Sheet

Options (cont'd)



Foam Marker - ATF0024D

- Supplied complete with 33 metres of hose, electrical cables with fitted
- Double sided deluxe model with solenoid controls
- In cab controller for left/right selection
- 24L high strength poly tank with safety valve
- Maximum foam production 330L per hour
- Working pressure 0.75 bar at 12 Volt DC
- Pressure relief valve set at 1 bar
- Water/Foam agent solution consumption 10.6 litres per hour
- Foam spreader made of flexible EPDM rubber to withstand accidental impacts
- Foam is generated at the boom ends and delivered in a series of blobs for longer lasting results



Quick Fill Kit - ATUQ3T32K

- 6 metres of 38mm suction hose
- Floating filter to prevent ingress of debris
- Venturi action anti-pollution suction head
- Max flow at 15 bar is 80 litre/min
- Up to 105 litre/min at 30 bar



Off Centre End Jet with Tap - ATPNSV100C

- Off centre nozzles can be fitted to allow for fenceline and channel spraying. Increases spray swath by 1 metre each side.
- Fitted with ball valve for easy manual control.



Versatile Boom - ABVL040

- 1.2 metre compact boom
- Sprays 4 metre swath width
- Compatible with any spot sprayer with pump - 7.5 litre/m or more
- Taps for 7 way nozzle control
- Versatility of spraying options
- Non-drip ball check filters



Poly Booms - ABP030/ABP040.

- | | |
|--|--|
| <ul style="list-style-type: none"> • Tough polyethylene provides excellent impact resistance • Nozzle guards provide excellent protection • Heavy duty construction for durability • UV stabilised for long outdoor life • Non-drip nozzle holders with 110° nozzles • Positive action breakaway | <ul style="list-style-type: none"> • Lightweight for easier handling • Proven corrosion and chemical resistance • Reinforced mounting points • Comes complete with nozzles, hoses and mounting brackets • Strong one piece truss design for durability, impact and crack resistance |
|--|--|



Steel Booms - ABM060/ABM080/ABM100

- | | |
|--|---|
| <ul style="list-style-type: none"> • Teejet compatible Quick connect nozzle caps • Non drip nozzle bodies • Spring loaded positive action breakaway • Fully plumbed • Built in nozzle protection • 6 & 8 metre booms hot | <ul style="list-style-type: none"> • dip galvanised steel construction • 10 metre powdercoated for durability • Adjustable boom mount brackets • Fitted with 110° Low Drift nozzles - standard. Other types available |
|--|---|