

PRESSURESCOUT

360L / 600L PRESSURE WASHER COMBO



Single Buddy Smart Reel® Version
360L



Single Buddy Smart Reel® Version
600L

360L & 600L PressureScout

SPRAYER SPECIFICATIONS

Item	Description	Details
Tank	360L 600L	UV stabilised chemical resistant polyethylene tank with integral sump. 15 year guarantee. AS2070:1999 compliant
Mounting	Frame	Galvanised forklift pockets and moulded lifting and tiedown handles
Pump	Bertolini Triplex Bertolini Triplex	12L/min 2000psi max 15L/min 3000 psi max
Motor	Honda GX200 Honda GX390 Yanmar L48 Yanmar L100	4 stroke, overhead valve, single cylinder. 4.1kW @ 3600rpm. 3 year warranty 4 stroke, recoil start, single cylinder. 8.7kW @ 3600rpm. 3year warranty Diesel recoil start, single cylinder. 3.5kW @ 3600rpm. 1 year warranty Diesel electric start, single cylinder. 7.4kW @ 3600rpm. 1 year warranty
Hose Reel	Single 30/50 metre manual Single 30/50 metre auto reel	Pwder-coated steel hose reel, full flow swivel, brass components, reel lock, rotating handle Buddy Smart Reel - 12/24V auto rewind hose reel with My-pace multiple speed remote, overrun protection, low voltage cut-out
Hose	3/8" hose	4000 psi rated with dual nozzle lance
Filter	1 1/4"	32 mesh screen filter, auto shut-off system for easy cleaning with full tank
Lid	250mm (2)	Threaded lid assembly with fixed labyrinth breather valve, UV stabilised
Drain	1 1/4"	High volume quick drain located at front (pump end) of tank
Detergent Tank	70L	with injector operated by dual lance gun

Tank Capacity	Length	Width	Height
360L	910mm	1100mm	840mm
600L	1300mm	1100mm	840mm