## PRODUCT SPECIFICATION SHEET **PRESSURE WASHER COMBO**







Single Buddy Smart Reel® Version 360L Single Buddy Smart Reel® Version 600L

## 360L & 600L PressureScout

## SPRAYER SPECIFICATIONS

ltem	Description	Details	
Tank	360L 600L	UV stabilised chemical resistant polyethylene tank with integral sump. 15 year guarantee. AS2070:1999 compliant	
Mounting	Frame	Galvanised forklift pockets and moulded lifting and tiedown handles	
Pump	Bertolini Triplex	12L/min 2000psi max	
	Bertolini Triplex	15L/min 3000 psi max	
Motor	Honda GX200	4 stroke, overhead valve, single cylinder. 4.1kW @ 3600rpm. 3 year warranty	
	Honda GX390	4 stroke, recoil start, single cylinder. 8.7kW @ 3600rpm. 3year warranty	
	Yanmar L48	Diesel recoil start, single cylinder. 3.5kW @ 3600rpm. 1 year warranty	
	Yanmar L100	Diesel electric start, single cylinder. 7.4kW @ 3600rpm. 1 year warranty	
Hose Reel	Single 30/50 metre manual	Pwder-coated steel hose reel, full flow swivel, brass components, reel lock, rotating handle	
	Single 30/50 metre auto reel	Buddy Smart Reel - 12/24V auto rewind hose reel with My-pace multiple speed remote, overrun protection, low voltage cut-out	
Hose	3/8" hose	4000 psi rated with dual nozzle lance	
Filter	1 1/4"	32 mesh screen filter, auto shut-off system for easy cleaning with full tank	
Lid	250mm (2)	Threaded lid assembley with fixed labyrinth breather valve, UV stabilised	
Drain	1 1⁄4"	High volume quick drain located at front (pump end) of tank	
Detergent Tank	17L	with injector operated by dual lance gun	

Tank Capacity	Length	Width	Height
360L	910mm	1100mm	840mm
600L	1300mm	1100mm	840mm