

PRODUCT SPECIFICATION SHEET

FIELDLINK ECO

400L / 600L / 800L 3-POINT LINKAGE SPRAYER



*Image for illustrative purpose only.

FieldLink Eco

SPRAYER SPECIFICATIONS

Item	Description	Details
Tank	400L 600L 800L	Australian made rotationally moulded UV stabilised chemical resistant polyethylene tank with integral sump. Graduated sight tube installed. 15 year guarantee. AS2070:1999 compliant
Lid	450mm / 250mm	450mm opening on main tank for easy access. 250mm on hand wash tank. "No-splash" breathers fitted
Mounting	Frame	Galvanised forklift pockets. Category 1, 2 and 3 pins
Pump	Bertolini Poly 2073	75L/min 215 psi max. Liquid fertiliser ready. Made in Italy. 3 year warranty.
Regulator	3-way Multi-controller	Arag regulator with glycerine filled pressure gauge for clear pressure readings, rotating knob for easy pressure adjustment
Flush Tank	N/A	
Hand Wash Tank	Built-in	Integrated 15L handwash tank with easy to access tap for safety
Hose	15m	Premium braided Australian made spray hose
Gun	AHG109	Powerjet spray gun with adjustable brass nozzle and accidental trigger lock
PTO Shaft	Adjustable	Supplied adjustable PTO shaft with guards
Booms		Ready to accept 4m / 6m / 8m booms
Custom Fit Options		See pricelist.

Tank Capacity	Length	Width	Height
400L	Dimensions still to be confirmed.		
600L	950mm	1220mm	1220mm
800L	950mm	1220mm	1405mm

* Dimensions do not include regulator or boom attachments. Height includes hose reel.